



SHTC #14 Heavy Duty Roofing Fastener-PH

**Material: Carbon Steel 1022A****Coating: Ruspert**

>> Product Description

SHTC#14 Heavy Duty Roofing Fastener-PH are designed to secure insulation to 16-22 gauge steel and wood decks. The fastener must achieve a penetration depth of 3/4" minimum. The fastener is also available pre-assembled with 3" Galvanized Steel Insulation Plates. Pre-assembled insulation fasteners and plates are fast to install and increase productivity in the mechanical attachment of roof insulation boards.


>> Features & Benefits

- Heavier shank and thread diameters than most standard roofing fasteners.
- Buttress thread design provides high pullout resistance.
- Sharp drill point for quick installation.

>> Corrosion Resistance

- 1800 hrs salt spray NSS resistance tested by SGS, appearance rating above 10 (ASTM B117-18)
- 15 cycle Kesternich test, no red rust (GB 9789)
- 1500hr salt spray NSS resistance test, no red rust (GB/T 10125)

Part NO.	Length	Thread	PKG(QTY)	Weight
#14X1-1/4-HD-PH	1-1/4"-32mm	Full	1000	13lbs (5.9kg)
#14X1-1/2-HD-PH	1-1/2"-38mm	Full	1000	16lbs (7.1kg)
#14X2-HD-PH	2"-50mm	Full	1000	19lbs (8.8kg)
#14X3-HD-PH	3"-75mm	Full	1000	27lbs (12.5kg)
#14X4-HD-PH	4"-100mm	3" (75mm)	1000	37lbs (16.6kg)
#14X5-HD-PH	5"-125mm	4" (102mm)	1000	45lbs (20.49kg)
#14X6-HD-PH	6"-150mm	4" (102mm)	1000	54lbs (24.39kg)
#14X7-HD-PH	7"-178mm	4" (102mm)	500	32lbs (14.3kg)
#14X8-HD-PH	8"-200mm	4" (102mm)	500	36lbs (16.4kg)
#14X9-HD-PH	9"-228mm	4" (102mm)	500	39lbs (17.6kg)
#14X10-HD-PH	10"-254mm	4" (102mm)	500	41lbs (18.6kg)
#14X11-HD-PH	11"-280mm	4" (102mm)	250	24lbs (10.7kg)
#14X12-HD-PH	12"-304mm	4" (102mm)	250	26lbs (11.6kg)



#3 PHILLIPS FLAT TRUSS HEAD

