



YN-995

WATERPROOF

NEUTRAL SILICONE STRUCTURAL SEALANT

- Neutral cure
- Excellent weatherability
- Odorless, non-corrosive
- Self-priming to most common building substrates
- 15 years warranty

Neutral Cure Silicone Sealant

is a high performance sealant suitable for sealing, bonding, repairing and mending of glass and window construction, double glazing in windows, aquariums, shower screens and sanitary ceramics. Neutral Silicone Sealant exhibits an excellent adhesion to glass tiles ceramics, fibreglass, aluminum, non-oily woods, painted surfaces, plastics and other nonporous surfaces.

Directions for use

1. Ensure all surfaces are clean, dry and grease-free. Remove all grit, oil, grease, detergents, flaking paint, any loose materials and old sealant.
2. Cut off tip of nozzle and cartridge. Screw on nozzle to cartridge.
3. Fit into caulking gun, apply on surface in steady flow.
4. If required smooth and shape sealant with spatula dipped in mild detergent.
5. Remove excess uncured sealant with a mineral turpentine soaked cloth. Fully cured excess sealant can be removed by trimming with a sharp knife.

>>Application Tips

- To obtain a smooth and neat finish, apply masking tape and remove before sealant cures.
- Paint surfaces completely before applying sealant.
- Before processing, observe the instructions in our product leaflets and safety data sheets.

>>Warning!

- Ensure good ventilation if used indoors.
- Contact of unvulcanised silicone sealant with eyes and mucuous membranes must be avoided as this will cause irritation.
- Prolonged contact with eyes, flush with water and consult physician if necessary.
- Keep out of reach of children.

>>Storage

- Store in dry and cool place below +30C (+90F).
- Use within 12 months from date of production.

